

Made in Germany

Modul STOU is specially formulated for use in agricultural tractors and various industrial machines. Designed for a uniform supply of diesel engines, manual transmissions, transfer cases, axle transmissions as well as hydraulic systems. It is also suitable for use in wet brakes and clutches.

Specification:

SAE-Klasse 10W-30

API CG-4/CF-4/CF/SF

API GL-4

ACEA E3

ACEA E7

Recommendations

Allison C4, Catepillar TO 2
Ford M2C 86B, 134 D, 159 B/C
Joon Deer J20 C,J20D, J27 D,
MAN 271
Komatsu B06-0002
Massey Ferguson M1135,M1139, M1143, M1144,
M1145
MB 228.1, 228.3
MIL-L-2104 D, Case New Holland MAT 3525,
3526, New Holland NH 024C, 030 C, New
Holland 410 B, 420 F

SPECIFICATIONS

Properties	Unit	Method	Typical value
Density @15°C	kg/m3	ASTM D1298	878
Kin. Viscosity @100°C	mm2/s	ASTM D445	11.3
Viscosity Index		ASTM D2270	140
Flash Point COC	°C	ASTM D92	220
Pour Point	°C	ASTM D97	-30
Sulphated Ash	% Wt	ASTM D 874	1.46

Custom code: 2710 9900

The above figures are those relating to normal manufacturing tolerances and do not constitute a specification

