

Modul Oil

Made in Germany

Modul UTTO is tractor fluid with outstanding multipurpose characteristics for agricultural tractors and industrial machines. It can be used as hydraulic oil as well as transmission oil, including wet brakes and clutches.

Specification:

SAE-Klasse 10W-40

API GL-4

Recommendations

Allison C4, Catepillar TO 2

Ford V C 134D, V2C 48-C2,

Joon Deer J20 C,

Komatsu B06-0002

Massey Ferguson CMS M1143.M1145

MIL-L-2105 A, New Holland 410B.420 A

Volvo WB 101

SPECIFICATIONS

| Properties | Unit | Method | Typical value |
|-----------------------|--------------------|------------|---------------|
| Density @15°C | kg/m ³ | ASTM D1298 | 884 |
| Kin. Viscosity @40°C | mm ² /s | ASTM D445 | 61 |
| Kin. Viscosity @100°C | mm ² /s | ASTM D445 | 9.8 |
| Viscosity Index | | ASTM D2270 | 148 |
| Flash Point COC | °C | ASTM D92 | 201 |
| Pour Point | °C | ASTM D97 | -39 |
| Sulphated Ash | % Wt | ASTM D 874 | 1.3 |

Basisoil:

Semi Synthetic base oils

Custom code: 2710 9900

The above figures are those relating to normal manufacturing tolerances and do not constitute a specification