

# Modul Oil

## Made in Germany

**Modul 0w40** is super low friction motor oil suitable for use in passenger car petrol and diesel engines. Top class fully synthetic components and special additives guarantee outstanding fuel saving and wear protection properties, also under constant and demanding use Suitable for use in high power sports vehicles.

### Specification:

SAE-Klasse 0W-40  
ACEA A2/B4  
API SN/CF  
LSAC GF-5

### Recommendations

BMW Longlife 01  
MB 229.5  
Porsche A 40  
Renault RN 0700, 0710  
VW 502.00, 505.00

## SPECIFICATIONS

Properties	Unit	Method	Typical value
Density @15°C	kg/m <sup>3</sup>	ASTM D1298	842
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D445	77
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D445	14.2
Viscosity Index		ASTM D2270	185
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-42
Total Base Number	mgKOH/g	ASTM D2896	10,0

**Basisoil:**  
HC-Synthetic

**Custom code:** 2710 9900

*The above figures are those relating to normal manufacturing tolerances and do not constitute a specification*