

Modul Oil

Made in Germany

Modul 15w40 is premium multigrade motor oil, suitable for use in passenger car petrol and diesel engines as well as truck diesel engines, both turbocharged and non-turbocharged/ Perfectly suitable as all-year oil for the mixed vehicle fleet. The universal properties also enable the application in construction machines, stationary engines, tractors and various small machines.

Specification:

SAE-Klasse 15W-40
API SL/CF/CG-4
ACEA A3/B4. E3

Recommendations

MB 228.1, 229.1
VW 501.01/505.00
MAN 271, 3275
Volvo VDS

SPECIFICATIONS

Properties	Unit	Method	Typical value
Density @15°C	kg/m ³	ASTM D1298	881
Kin. Viscosity @40°C	mm ² /s	ASTM D445	110
Kin. Viscosity @100°C	mm ² /s	ASTM D445	14.6
Viscosity Index		ASTM D2270	120
Flash Point COC	°C	ASTM D92	225
Pour Point	°C	ASTM D97	-24
Total Base Number	mgKOH/g	ASTM D2896	8.7
Sulphated Ash	%Wt	ASTM D874	1.26

Basisoil:

Mineral base oils

Custom code: 2710 9900

The above figures are those relating to normal manufacturing tolerances and do not constitute a specification