

Modul Oil

Made in Germany

Modul 75w90 is high performance gear oil based on high quality fully synthetic and HC synthetic components in combination with advanced additive technology. Suitable for use in modern manual transmissions and axle drives. Please note: Not Suitable for use in stepped automatic transmissions. DCT/DSG transmissions or CVT transmissions.

Specification:

SAE-Klasse 75W-90
API GL4/5

Recommendations

MAN 3343 M, MAN 341 Z-2, MAN 342 M-2
MB 235.6.235., 235.1, 235.5
MIL-L-2105 D. MIL-L-2105 E
Scania STO 1:0
Volvo 1273.10
ZF TE-ML 01L, 02B, 05A, 07A, 08, 12A
16B, 16C, 16D, 17A, 17B

SPECIFICATIONS

Properties	Unit	Method	Typical value
Density @15°C	kg/m ³	ASTM D1298	878
Kin. Viscosity @40°C	mm ² /s	ASTM D445	94.2
Kin. Viscosity @100°C	mm ² /s	ASTM D445	15.2
Viscosity Index		ASTM D2270	171
Flash Point COC	°C	ASTM D92	201
Pour Point	°C	ASTM D97	-36

Basisoil:

Semisynthetic base oils

Custom code: 2710 9900