

Modul Oil

Made in Germany

Modul ATF DEXRON III is a fluid produced using carefully selected and balanced components and recommended for automatic transmissions, power steering, hydraulically assisted steering and torque convertors, whenever it is required a product able to satisfy the requirements of GENERAL MOTORS Dexron III. It is also used as an hydraulic oil over a large temperature range for applications in the automotive, industry and marine fields of red color

Specification:
ATF Dextron III

Recommendations

GM DEXRON III-IIIIG

ZF TE-ML 02F, 03D, 04D, 09B, 11B, 14A, 17C

VOITH G607

ALLISON C4

CAT TO2

MB 236.5-236.9

FORD MERCON

SPECIFICATIONS

Properties	Unit	Method	Typical value
Density @15°C	kg/m ³	ASTM D1298	860
Kin. Viscosity @40°C	mm ² /s	ASTM D445	30.4-36
Kin. Viscosity @100°C	mm ² /s	ASTM D445	6.4-7.9
Viscosity Index		ASTM D2270	180
Flash Point COC	°C	ASTM D92	195
Pour Point	°C	ASTM D7346	-45

Basisoil:
Mineral base oils

Custom code: 2710 9900

The above figures are those relating to normal manufacturing tolerances and do not constitute a specification